



# **Adina Industries Co., Ltd**

Head Office: Room 525-527, Xihu International Trade Center, Shangcheng District, Hangzhou City, Zhejiang Province, China.

Factory address: Chen'aoli Industrial Area, Damaiyu Street, Yuhuan City, Zhejiang Province, China. web: www.adinaindustries.com E-Mail: info@adinaindustries.com

# **PLASTIC RECYCLING MACHINE SOLUTION Adina Industries Co., Ltd**





#### ADINA INDUSTRIES

ADINA INDUSTRIES was established in 2016 which is a professional manufacturer of plastic recycling machinery in Zhejiang city, China. Worksite area of 4000m2, office 300m2 and 50+ employees. Pursuing innovation and high quality, we specialize in plastic waste crushing, washing and drying lines, turn-key plant for recycling varies plastics, granulating machines, shredding and crushing system, customized equipment and components.

With over 08 years of experience in plastic recycling & processing equipment, We have supplied machines to 30+ countries: USA, Russia, Mexico, Chile, Brazil, Vietnam, Saudi Arabia, Egypt, Romania, UAE.,etc. We keep upgrading technology to be more competitive to supply more durable machines to customers all over the world. We customize and design machines for you according to your specified requirement.

ADINA INDUSTRIES will be faithful to be your best cooperative partner in plastic recycling plant and create the most value for you!

# WHY CHOOSE US?

#### **Turnkey Solution**

Suggest best solution on machine configuration and design the recycling plant based on clients requirements. Offer affordable price, less advertising costs, more benefits to users.

#### Sincere communication

No bragging, No exaggeration. We provide suggestion based on our actual production experience and feedback from users.

#### Quality assurance

With CE standard, ensure security protection for both operators and machines. Mechanical and electrical components are of trusted brand and our long-term suppliers. Times of careful test running before delivery.

#### Quick Response & Service

Our dynamic term of specialists and technicians are available for online support. Providing technical assistance in installation,commission and training. Quick response and technician standby for service abroad if needed.







# ADINA INDUSTRIES PP/PE FILM, PP WOVEN BAGS/RAFFIA RECYCLING WASHING LINE PP/PE 薄膜, PP编织袋回收清洗生产线


#### 设备简介 Equipment Introduction

Highly and normally contaminated PE packing film, agricultural film, drip irrigation pipes, PP jumbo bags, raffia, go though size reduction(shredder/crusher), intensive cleaning by friction (friction washer), rinsing (flotation tank), and drying (hot-air/centrifugal dryer/squeezer), become clean flakes for downstream extrusion and pelletizing process. We supply a variety of plastic washing lines differing in capacity, and your specified requirement.




#### 包含单机 Machines Included





Shredder



Electrical control cabinet 11 集中控制柜

2



) High-speed friction washer 6 高速搓洗机

9 Squeezer 挤干机

## 生产线估算参数 Estimated Plant Parameters

| Capacity(kg/h)<br>产量(kg/h) | Power installed(kw)<br>安装功率(kw) | Required area(m²)<br>工厂面积(m²) | Manpower<br>人力 | Water supply(m²/H)<br>用水量(m²/H) | Final Products<br>成品 |
|----------------------------|---------------------------------|-------------------------------|----------------|---------------------------------|----------------------|
| 200-300                    | 110-160                         | 350                           | 2-3            | 4-5                             | Moisture:            |
| 400-600                    | 160-230                         | 400                           | 3-4            | 8-10                            | 3-10%                |
| 800-1000                   | 280-500                         | 750                           | 4-6            | 15–20                           | Particle size:       |
| 1500                       | 380-600                         | 1000                          | 6-8            | 20-30                           | 60-100mm             |



Centrifugal dryer



Squeezer dryer



# PP/PE RIGID PLASTICS RECYCLING WASHING LINE PP/PE 硬杂料回收清洗生产线

#### 设备简介 Equipment Introduction

Rigid waste plastics such as HDPE milk bottles, shampoo bottles, chemical barrels, oil pots, PP injection containers, baskets, basins,.etc, go though size reduction (shredder/crusher), intensive cleaning by friction (friction washer), rinsing (flotation tank), and drying (hot– air/centrifugal dryer), become clean flakes for downstream extrusion and pelletizing process. We supply a variety of plastic washing lines differing in capacity and your specified requirement.







沉淀漂洗池

5

8

Sink-float washing tank

)Hot−air pipe drying system )管道烘干系统



6 High-speed friction washer 高速搓洗机

ADINA INDU

9 Storage silo 过渡料仓

#### 生产线估算参数 Estimated Plant Parameters

| Capacity(kg/h )<br>产量(kg/h) | Power installed(kw)<br>安装功率(kw) | Required area(m²)<br>工厂面积(m²) | Manpower<br>人力 | Water supply(m²/H)<br>用水量(m²/H) | Final Products<br>成品   |
|-----------------------------|---------------------------------|-------------------------------|----------------|---------------------------------|------------------------|
| 200-300                     | 100                             | 300                           | 2-3            | 4-5                             |                        |
| 400-500                     | 115                             | 300                           | 2-3            | 4-5                             | Moisture:              |
| 800-1000                    | 125                             | 500                           | 3–5            | 6-8                             | 1−2%<br>Particle size: |
| 1300-1500                   | 180                             | 600                           | 3–5            | 8-10                            | 8-16mm                 |
| 1800-2000                   | 250                             | 800                           | 3-5            | 10-15                           |                        |









PET BOTTLES RECYCLING WASHING LINE PET 瓶回收清洗生产线







### 设备简介 Equipment Introduction

PET bottle washing recycling line is specially designed for produce PET flakes for fiber use. The flakes can used for 2-D,3-D PSF,filament yarn,PET strap,PET sheet or PET film. It can adopt the PLC automatic control for the full line. Automatic material sorting system and color sorting system can be choose optionally. We can configure the machine line according to the raw material and customer needs.



Bale breaker 拆包机













# 生产线估算参数 Estimated Plant Parameters

| Capacity(kg/h)<br>产量(kg/h) | Power installed(kw)<br>安装功率(kw) | Required area(m²)<br>工厂面积(m²) | Manpower<br>人力 | Water supply(m³/h)<br>用水量(m³/h) | Total impurity<br>总含杂 | Flakes size<br>瓶片尺寸 |
|----------------------------|---------------------------------|-------------------------------|----------------|---------------------------------|-----------------------|---------------------|
| 500                        | 155                             | 300                           | 2-3            | 4-5                             |                       | 12–16mm or          |
| 1000                       | 285                             | 500                           | 7–8            | 5-6                             | <br>100ppm            | according to        |
| 2000                       | 485                             | 1000                          | 10-12          | 10-15                           |                       | customer needs      |

#### 占地、水电气及人员需求重 Estimated Plant Parameters

| Capacity(kg/h )<br>产量(kg/h) | Power installed(kw)<br>安装功率(kw) | Required area(m²)<br>工厂面积(m²) | Manpower<br>人力 | Steam volume(kg/h)<br>蒸汽量(kg/h) | Compressed Air(m³/min)<br>蒸汽量(m³/min) | Water supply(m³/h)<br>用水量(m³/h) |
|-----------------------------|---------------------------------|-------------------------------|----------------|---------------------------------|---------------------------------------|---------------------------------|
| 500                         | 220                             | 400                           | 8              | 350                             | 4                                     | 1                               |
| 1000                        | 500                             | 750                           | 10             | 500                             | 10                                    | 3                               |
| 2000                        | 700                             | 1000                          | 12             | 800                             | 15                                    | 5                               |



# ML PLASTIC FILM RECYCLING PELLETIZING LINE WITH THERMAL-COMPACTOR 塑料薄膜压实造粒线

#### 设备简介 Equipment Introduction

ML series of multifunctional plastic recycling pelletizing line fits for PE PP film (printed, non-printed), bags, raffia, pre-shredded EPS foam and EPE, and flexible film flakes from washing line. It combines size reduction and pre-heat function in the thermal-compactor to guarantee stable and efficient feeding materials into the extruder. We supply customized machine design and components according to the characteristics of your raw materials and specific requirement.





#### 主要规格 Main technical parameters

| Model             | 型号        | ML85     | ML100    | ML130    | ML160    | ML180     |
|-------------------|-----------|----------|----------|----------|----------|-----------|
| Screw diameter(mm | )螺杆直径(mm) | 85       | 100      | 130      | 160      | 180       |
| L/D               | 长径比       | 10~38:1  | 10~38:1  | 10~38:1  | 10~38:1  | 10~38:1   |
| Rotary speed      | 转速        | 10-150   | 10-150   | 10-150   | 10-150   | 10-150    |
| Compactor         | 密实机直径     | EQUIPPED | EQUIPPED | EQUIPPED | EQUIPPED | EQUIPPED  |
| Capacity(kg/h)    | 产量(kg/h)  | 180-250  | 300-400  | 500-600  | 700-800  | 1000-1500 |





# SJ SINGLE-SCREW PLASTIC RECYCLING PELLETIZING LINE FOR RIGID PLASTICS 硬杂料造粒线

#### 设备简介 Equipment Introduction

SJ series of plastic recycling pelletizing line fits for rigid flakes such as PE PP agglomerates, ABS PC PS regrinds, squeezed flakes from washing line. Highly automatic control and easy operation, high output up to 1500kg/h. combination of two or three extruders helps to promote pellets quality and production stability. We supply customized machine design and components according to the characteristics of your raw materials and specific requirement.

0.0



#### 主要规格 Main technical parameters

00

| Model                       | 型号       | SJ90    | SJ100   | SJ120   | SJ150   | SJ160   | SJ180    | SJ200     |
|-----------------------------|----------|---------|---------|---------|---------|---------|----------|-----------|
| Screw diameter(mm) 螺杆直径(mm) |          | 90      | 100     | 120     | 150     | 160     | 180      | 200       |
| L/D                         | 长径比      | 10~38:1 | 10~38:1 | 10~38:1 | 10~38:1 | 10~38:1 | 10~38:1  | 10~38:1   |
| Rotary speed                | 转速       | 10-150  | 10-150  | 10-150  | 10-150  | 10-150  | 10-150   | 10-150    |
| Capacity(kg/h)              | 产量(kg/h) | 150-200 | 200-300 | 300-450 | 500-650 | 650-800 | 800-1000 | 1000-1500 |



# 100000-000







THUNDUSTR





SS series single shaft shredder is an economy choice for size reduction of regular plastics: soft film, jumbo bags, raffia, fiber, fish nets, and rigid large start-up lumps, extrusion scraps, offcut, thick pipes, hollow barrels, differ in rotor design. Hydraulic powered pushing plate move forward to push materials against the rotor to be shredded. Highly wear-resisting rotor and knives help users to save cost and maintenance frequency as much as possible.

- Siemens PLC control, first-line brands of electric elements, long service life.
- Various rotor designs according to characteristics of your raw materials and desire.
- First-line brands of motor and gear box, guarantee powerful and stable running.
- Movable feeding hopper can be mounted for long pipes to adjust angle freely.



#### 主要规格 Main technical parameters

| Model           | 型号       | Ss600   | SS800   | SS1000   | SS1200    | SS1500    |
|-----------------|----------|---------|---------|----------|-----------|-----------|
| Motor power(kw) | 功率(kw)   | 22/30   | 37/45   | 55/75    | 75/90     | 110/132   |
| Capacity(kg/h)  | 产量(kg/h) | 200-400 | 500-800 | 800-1000 | 1000-1500 | 1500-2000 |

## DSS DOUBLE-ROTOR SHREDDER 双辊撕碎机





#### 主要规格 Main technical parameters

| Model           | 型号       | DSS600  | DSS800   | DSS1000   | DSS1200   | DSS1500   |
|-----------------|----------|---------|----------|-----------|-----------|-----------|
| Motor power(kw) | 功率(kw)   | 30*2    | 37*2     | 55*2      | 75*2      | 90*2      |
| Capacity(kg/h)  | 产量(kg/h) | 500~800 | 800~1200 | 1000~1200 | 1200~1500 | 2000~3000 |




#### 设备简介 Equipment Introduction

With two rotors (as in the single-rotor shredder) mounted in a chamber, it achieves ideally double output compared with SS single rotor shredder, designed for soft film.





# **HEAVY-DUTY SINGLE-ROTOR SHREDDER WITH SWING RAM** 重型摆臂单轴撕碎机



#### 设备简介 Equipment Introduction

YPS series heavy-duty single shaft shredder is suitable for both flexible film, jumbo bags, raffia, fiber, fish nets, and rigid large startup lumps, extrusion scraps, offcut, pipes, hollow barrels.,etc. Measuring 500mm in rotary diameter and up to 1450 in length, YPS rotor easily meets your high throughput desires. Hydraulic powered swing ram promotes feeding efficiency. Highly wear-resisting rotor and knives help users to save cost and maintenance frequency as much as possible.

- Siemens PLC control, first-line brands of electric elements, long service life.
- Various rotor designs according to characteristics of your raw materials and desire.
- First-line brands of motor and gear box, guarantee powerful and stable running.
- Distinctive swing arm allows more space for materials and press for higher feeding efficiency.







#### 主要规格 Main technical parameters


| Model            | 型号       | YPS850  | YPS1050  | YPS1250   | YPS1450   |
|------------------|----------|---------|----------|-----------|-----------|
| Motor power( kw) | 功率(kw)   | 55      | 75       | 90        | 110       |
| Capacity(kg/h)   | 产量(kg/h) | 500-600 | 800-1000 | 1000-1500 | 1500-2000 |


## **HEAVY DUTY LONG PIPE SHREDDER** 重型长管材撕碎机



#### 应用 Application

Large diameter pipes such as PE, PVC, PP, and shreds of large diameter bellows.





#### 主要规格 Main technical parameters

| Model                        | 型号         | YPS800      | YPS1000 | YPS1500  |
|------------------------------|------------|-------------|---------|----------|
| Rotor rotary diameter(mm)    | 转子回转直径(mm) | Φ800        | Φ980    | Φ1430    |
| Motor power( kw)             | 功率(kw)     | 2×37        | 2×45    | 2×55     |
| Applicable pipe diameter(mm) | 适用管径(mm)   | < \$\phi630 | < \$00  | < o 1000 |





#### 设备简介 Equipment Introduction

DS Series double shaft shredders can handle a wide range of thin and hollow materials such as car tires, plastic bags, film, car bumpers, barrels, drums, wood pallets, woven and non-woven fabrics. High throughput and with overload protection.. Compared to single shaft shredder, this series has lower speed, higher torque, and higher efficiency. It excels in size reducing industrial waste, MSW, electronic waste, waste household appliances and other mixed wastes. Its structure is relatively compact and maintenance-friendly with maintenance door that provides full access to crushing chamber and bearing housing. Because the shredder is screen less, it is often used as primary shredding, and its shredded particle size depends on the blade thickness.

#### 主要规格 Main technical parameters

| Model           | 型号       | DS650   | DS800    | DS1000    | DS1200        | DS1600        |
|-----------------|----------|---------|----------|-----------|---------------|---------------|
| Motor power(kw) | 功率(kw)   | 15/22   | 18.5/30  | 22 × 2/45 | 37 × 2/45 × 2 | 45 × 2/55 × 2 |
| Capacity(kg/h)  | 产量(kg/h) | 500~800 | 800~1200 | 1000~1200 | 1200~1500     | 2000~3000     |

# CRUSHER 破碎机



#### 设备简介 Equipment Introduction

HVC series of heavy-duty crusher is designed for grinding thin plastics such as PE PP film, bags, raffia, woven and non-woven, thin PVC pipes, sheets, profiles, hollow barrels, PET bottles, etc to achieve massive output. A variety of rotor designs according to material characteristics and your desire for downstream process.



#### 主要规格 Main technical parameters

| Model                         | 퓇号       | HVC500/800 | HVC600/800 | HVC600/1000 | HVC700/1000 | HVC600/1200 | HVC700/1200 | HVC800/1200 |
|-------------------------------|----------|------------|------------|-------------|-------------|-------------|-------------|-------------|
| Rotor Diameter(mm)            | 回转直径(mm) | Φ500       | Φ600       | Φ600        | Φ700        | Φ600        | Φ700        | Φ800        |
| Rotor Knives(pcs)             | 动刀(片)    | 3×2,5×2    | 3×2,5×2    | 3×2,5×2     | 5×2         | 5×2         | 5×2,7×2     | 5×2,7×2     |
| Stator Knives(pcs)            | 定刀(片)    | 2x2        | 2x2        | 2x2         | 2x2         | 2x2         | 2x2         | 2x2         |
| Cutting Chamber Dimension(mm) | 破碎箱体(mm) | 500x780    | 600x780    | 600×980     | 700×980     | 600x1180    | 700x1180    | 800x1180    |







# FILM EXTRUDER 薄膜挤干机



#### 设备简介 Equipment Introduction

Pipe crusher is designed for grinding PVC pipes, sheets, profiles, and thin HDPE PPR pipes. With air conveying and dust collection system you can keep your workshop clean.



#### 设备简介 Equipment Introduction

Film squeezer is designed for further drying of thin film and raffia that coming from upstream washing line with high moisture. By power of inner pressing screw materials are squeezed, heated, and diced on the exit die face into semi-melted granules, which are more easily to be fed into the downstream extruder for pelletizing.



#### 主要规格 Main technical parameters

| Model           | 型号       | JG250   | JG300   | JG320   | JG350    |
|-----------------|----------|---------|---------|---------|----------|
| Motor power(kw) | 功率(kw)   | 75/90   | 110     | 160     | 200      |
| Capacity(kg/h)  | 产量(kg/h) | 300-400 | 400-600 | 600-800 | 800-1000 |

# 10000





0000

# **AUXILIARY MACHINE SERIES** 辅机系列



Knife sharpener 磨刀机





Milling Machine 磨粉机

Grinder 磨粉机







crusher 粉碎机



Agglomerator 团粒机

mixing dryer 混合干燥机